



TEHNIČNI PODATKI - TECHNISCHE DATEN - TECHNICAL DATA

Premer cevi – Rohrdurchmesser – Pipe diameter:	14 – 17 mm
Razdalja med cevmi – Verlegeabstand – Pipe spacing:	50, 100, 150, 200 mm
Izolacijski material – Dämmstoff – Insulation material:	EPS
Ozn. po standardu – Bezeich. nach Norm – Designation acc. to norm:	EPS-EN 13163-T2-L1-W1-S1-P3-DLT(1)5-CS(10)150-BS250-DS(N)5
Koristna velikost – Nutzgröße – Usable size:	1300×800 mm
Koristna površina – Nutzoberfläche – Usable surface:	1,04 m ²
Skupna velikost – Gesamtgröße – Total size:	1350×850 mm
Skupna debelina – Gesamtdicke – Total tickness:	53 mm
Skupna debelina izolacije – Gesamtisolationdicke – Total insulation tickness:	32 mm
Koeficient toplotne prevodnosti – Wärmeleitfähigkeit – Thermal resistance factor:	0,034 W/(m.K)
Toplotna upornost plošče – Wärmedurchlasswiderstand – Heat admission resistance:	0,94 m ² K/W
Tlačna trdnost (10% def.) – Druckspannung (bei 10% Stauchung) – Compressive stress (10% def.):	150 kPa
Upogibna trdnost – Biegefestigkeit – Bending strangth:	200 kPa
Temp. obstojnost oblike – Wärmeformbeständigkeit – Heat form resistance:	80 °C
Razred gorljivosti – Brandverhalten – Fire classification – EN 13501-1:	E
Razred gorljivosti – Brandverhalten – Fire classification – DIN 4102:	B1
Material folije – Folienwerkstoff – Foil material:	PS
Debelina folije – Foliendicke – Foil tickness:	0,4 mm
Barva folije – Folienfarben – Foil colour:	črna – schwarz – black
Prekrivanje folije – Folienüberlappung – Foil overlap:	50 mm
Pakiranje – Verpackungseinheit – Packaging unit:	10,4 m ²
Pakiranje kos/karton – Verpackungseinheit in Stück/Karton – Packaging unit in pieces/carton:	10
Velikost kartona – Maße karton – Carton dimensions:	1420×880×435 mm