



Hladilniška
krilna vrata

Cold store
folding door

VRATA HK

Hladilniška krilna vrata

Cold store folding door

Opis

Vrata so izdelana iz krožno polirane nerjavne pločevine in toplotno izolirana: krilo z vložkom iz trde EPS pene, podboj pa s PU peno. Tesnilo iz silikonske gume je primerno za temp. od -40 do +200 °C. Vrata za zamrzovalne komore imajo večjo debelino krila in so opremljena z dvojnimi tesnilom, zaradi preprečevanja zmrzovanja tesnila pa je podboj električno ogrevan. Tlačni aji z dviznim delovanjem ter zapiralo s ključavnico in notranjim varnostnim gumbom za odpiranje v sili so izdelani iz korozijsko odpornih materialov. Podboj vrat je lahko prirejen za vgradnjo transp. tira.

Namen

Toplotno izolirana in higiensko neoporena vrata so pomemben del opreme hladilnih prostorov v dejavnostih kot so:

- predelava mesa in rib
- mlekarstvo
- shranjevanje sadja in zelenjave
- vinarstvo
- pekarstvo in testeninarstvo
- skladiščenje globoko zmrznjene hrane
- gostinstvo
- farmacija in industrija kozmetike
- cvetličarstvo

Vgradnja

Vrata so primerna za vgradnjo v zidano ali panelno steno. V prvem primeru je treba pri pripravi gradbene odprtine upoštevati tudi debelino toplotne izolacije prehoda.



Description

The door is made of circularly polished stainless steel and are thermally insulated: the folding with hard EPS foam filling, the frame with PU foam. Silicone rubber gasket is suitable for temperature range from 40 to +200 °C. The door of the refrigeration chamber is thicker, has double gasket, the frame is heated to prevent the freezing of the gasket. Rising hinges, spring bolt, lock and safety button on the inside are made of rust-resistant materials. The door frame can be adapted for transporting track installation.

Purpose to use

Thermally insulated and hygienic door is an important part of cold store equipment in branches, such as:

- meat and fish processing industry
- dairies
- storage of fruit and vegetables
- vine trade
- bakeries and dough production
- storing of deep-frozen food
- hotel trade and catering
- pharmacy and cosmetics industry
- floriculture

Installation

The door can be installed into a constructed or panel wall. In the first case the thickness of thermal insulation of the passage must be considered at making the doorway.



Stand. mere / Standard sizes

širina odprtine: opening width:	80, 90, 100 in 120 cm
višina odprtine: opening height:	200, 220 in 240 cm
debelina krila: folding thickness:	8, 13 in 18 cm