

# DECLARATION OF PERFORMANCE

HI - 120/18-01

Unique identification code of the product:

**IBITOL HS**

Intended use:

**cold bitumenous primer before application of bituminous products in general**

Manufacturer:

**FRAGMAT TIM d.o.o., Spodnja Rečica 77, SI-3270 Laško  
Tel.: + 386 3 73 44 500; Fax: + 386 3 73 44 618**

Declared performances:

| Essential characteristics                             | Performance   |      |             |
|---|---------------|------|-------------|
|   | Method        | Unit | Value       |
| Density (at 20°C)                                     | ISO 2811-1    | g/ml | 0,90 – 0,94 |
| Bitumen content                                       | EN 13358      | %    | 50 - 60     |
| Flow time by use of flow cups<br>(Ø 4 mm; 25°C±0,5°C) | EN ISO 2431   | s    | 20 - 40     |
| Drying time   | EN ISO 9117-3 | h    | ≤ 3         |
| Flash point   | EN ISO 13736  | °C   | 30 – 40     |

Signed for and on behalf of the manufacturer by:

Laško, 15.03.2016

Head of production:

Janez Potočnik, ing.

FRAGMAT TIM d.o.o., Spodnja Rečica 77, SI-3270 Laško; tel.:+386 3 734 45 00, fax.:+386 3 734 46 18; www.fragmat.si

Replace: N° HI - 120/16-01

**FRAGMAT** 

**SI**   
ISO 9001 Q-749  
ISO 14001 E-155